

# Pharmacy Refrigerator

**HYC-118A**



## LED Display

Microprocessor control, digital display and temperature adjustment with an increment of 0.1 °C.

## Multiple Alarm Functions

Capable of alerting failures due to high and low temperature, sensor error, power failure, low battery, door ajar and remote alarm.

## Ergonomic Design

810mm cabinet height makes it easy to place under test bench, saving storage space.

## Lockable Design

Safety lock to prevent unauthorized access.

## Superior Cabinet Temperature Uniformity, Auto Defrost

The test point of performance in the cabinet increased from 2 points to 9 points.

## Energy Efficient Hydrocarbon (HC) Refrigeration System

Optimised refrigeration system, utilising high-efficiency HC compressor significantly reduces energy consumption.

## Greener by Design

HC refrigerants are natural non-toxic and more environmentally friendly.

## Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,  
Qingdao, 266109, P.R. China  
Tel: +86-0532-88935593  
Website: [www.haiermedical.com](http://www.haiermedical.com)



Haier Biomedical  
International



Haier Biomedical  
International



@haiermedicalint



Haier Biomedical  
International



Haier Biomedical  
International

## Specifications



### HYC-118A

#### Technical Data

Cabinet Type	Upright, glass door
Climate Class	N
Cooling Type	Forced air cooling
Defrost Mode	Auto
Refrigerant	HC
Noise (dB (A))	41

#### Performance

Temp Range (°C)	2-8
-----------------	-----



#### Control

Controller	Microprocessor
Display	LED

#### Electrical Data

Power Supply (V/Hz)	220~240/50/60	115/50/60
Power (W)	230	230
Electrical Current (A)	1.5	1.5

#### Construction

Capacity (L/Cu.Ft)	118/4.2	
Net/Gross Weight (approx)	(kg)	46/51
	(lbs)	101.5/112.5
Interior Dimension (W*D*H)	(mm)	515*415*630
	(in)	20.3*16.3*24.8
Exterior Dimension (W*D*H)	(mm)	597*635*810
	(in)	23.5*25.0*31.9
Packing Dimension (W*D*H)	(mm)	680*690*910
	(in)	26.8*27.2*35.8

#### Accessories

Caster	Y
Foot	Y
Porthole	Y
Shelves/Drawers	3/1

#### Alarms

High/Low Temp	Y
Remote Alarm	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
Door Ajar	Y

#### Certification

CE	Y
UL	Y