

Active Temperature Controlled RKN Container



RKN-AT1

Scope of Application :

This product is applicable for international aviation cold chain transportation of drugs, vaccines, medicines, biological products, raw materials, high-end fresh food and other products which require strict temperature control.

Innovative Design

- Safe, reliable and secure
- Superior temperature uniformity
- Robust construction
- Automatic switching between AC power supply and built-in battery power supply

Qingdao Haier Biomedical Co.,Ltd.
Qingdao HB TempCon Aviation Co., Ltd

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: 0532-88935595
E-mail: inquiry@haierbiomedical.com;
aviation@haierbiomedical.com
Website: www.haiermedical.com



HB TempCon Aviation



HB TempCon Aviation



HB TempCon Aviation



HB TempCon Aviation





HB TempCon Aviation

Qingdao HB TempCon Aviation Co., Ltd. is a subsidiary of Haier Biomedical, which specializes in the R & D, sales, leasing, operation and maintenance of temperature controlled RKN containers and land / marine active and passive temperature controlled equipment.


Active Temperature Controlled RKN Container

Product Advantages

 Robust construction with advanced technology to ensure reliable quality and stable performance

 Superior internal temperature uniformity

 Prevent internal temperature deviation and ensure the temperature uniformity under extreme environmental temperature changes

 Cost-Effective Performance

Specifications



Power	
Supports automatic switching between external AC power supply and built-in battery power supply, which is convenient to use and simple to operate	
Recharging power supply	100-240V AC, 50-60Hz
Maximum charging time (h)	10 (fast charging)
Maximum power during charging (w)	1,850

Temperature Control Performance

The temperature management system, developed independently, achieves accurate temperature control through compressor refrigeration and electric heating innovative air circulation system to effectively balance the temperature difference

Temperature range	Internal temperature tolerance	
0°C~+25°C (+32°F to +77°F)	At set temperature +2°C~+10°C (+35.6°F to +50°F), Tolerance +/-3°C (+/-5.4°F)	
	At set temperature +10°C~+20°C (+50°F to +68°F), Tolerance +/-5°C (+/-9°F)	
Battery capacity	Operating ambient temperature	Storage ambient temperature
When the ambient temperature is 25°C (77°F), the set temperature is 5°C (41°F), the container can operate for more than 50 hrs.	-20°C~+43°C (-4°F to +109.4°F)	-40°C~+50°C (-40°F to +122°F)

Construction

Internal effective volume	Exterior dimensions (L*W*H)	Interior dimensions (L*W*H)	Door opening (L*H)
2m ³ (70.6 foot ³)	2005*1534*1620mm (78.9*60.4*63.8in)	1294*1273*1264mm (50.9*50.1*49.8in)	1294*1264mm (50.9*49.8in)

Weight

Tare weight	Operational maximum gross weight	Maximum payload
640kg (1410lbs)	1588kg (3500lbs)	948kg (2090lbs)

Data Recording

Data recording function: internal and external temperature, door opening times, alarm information through USB port

Others

Applicable Aircraft Models: A300, A310, A330, A340, A380, B747, B767, B777, DC10, IL86, MD11, L1011 as key examples

Note

Tare weight and maximum payload might vary due to load variations and maintenance

*Typical prototype test data

Haier Biomedical reserves the right to change products and specifications without prior notice.